



HV jacks

Z

These robust REMA hydraulic jacks are designed for load capacities ranging from 2 to 50 tons.

Properties

- The desired height can easily be adjusted by means of a spindle.
- Relief valve for overload prevention.
- Can be used exclusively in upright position, in the temperature range -5°C to 45°C.
- Do not use in aggressive environment (bases, acids etc.)
- Not suitable for prolonged loading.
- Not suitable for using horizontal.

type	ref. no.	safe working load (kg)	minimum height (mm)	maximum height (mm)	range (mm)	spindle length (mm)	weight (kg)
HV - 2.0	2750016	2.000	158	298	90	50	2.3
HV - 4.0	2750032	4.000	180	350	110	60	3.3
HV - 6.0	2750050	6.000	200	395	125	70	4.6
HV - 8.0	2750080	8.000	200	405	125	80	5.5
HV - 10.0	2750100	10.000	200	405	125	80	6.0
HV - 12.0	2750125	12.000	205	405	120	80	7.2
HV - 16.0	2750160	16.000	220	440	140	80	9.0
HV - 20.0	2750200	20.000	233	456	143	80	11.5
HV - 32.0	2750300	32.000	280	460	180	-	18.0
HV - 50.0	2750500	50.000	300	480	180	-	33.0