



TRV roller carriages

V

Properties

- Ideal for an easy and safe handling of loads.
- Nylon rollers running on ball bearings.
- Nylon rollers will not damage floors.
- Platforms have anti-slip rubber coatings.
- Can be easily placed or positioned by means of the hand grip.

| type | ref. no. | safe working load (kg) | number of rollers | number of axes | roller Ø x width (mm) | platform L x W x H (mm) | weight (kg) |
|----------|----------|------------------------|-------------------|----------------|-----------------------|-------------------------|-------------|
| TRV - 10 | 4250021 | 1000 | 4 | 2 | 100 x 35 | 330 x 220 x 120 | 7 |
| TRV - 20 | 4250023 | 2000 | 8 | 2 | 100 x 35 | 330 x 220 x 120 | 8 |
| TRV - 25 | 4250025 | 2500 | 2 | 2 | 85 x 90 | 210 x 100 x 105 | 4 |
| TRV - 30 | 4250027 | 3000 | 4 | 2 | 85 x 85 | 330 x 300 x 120 | 10 |
| TRV - 60 | 4250029 | 6000 | 6 | 3 | 85 x 85 | 260 x 230 x 105 | 12 |



TRZ carriages with caster

V

Roller carriages fitted with steering rollers for good manoeuvrability.

- Specifications**
- TRZ-102** 2 steer nylon rollers Ø 75 x 46 mm.
2 rigid nylon rollers Ø 100 x 35 mm.
 - TRZ-104** 4 steer nylon rollers Ø 75 x 46 mm.

| type | ref. no. | safe working load (kg) | platform L x W x H (mm) | weight (kg) |
|---------|----------|------------------------|-------------------------|-------------|
| TRZ-102 | 4250031 | 1000 | 430 x 340 x 120 | 13 |
| TRZ-104 | 4250033 | 1000 | 430 x 340 x 120 | 14 |



TKV / TBV corner movers for handling cabinets and bureau furniture

V

REMA roller carriages for handling cabinets and office furniture for handling loads with a maximum 600 kg with or without legs.

Properties

- 1 set consists of 4 units.
- Ease of steering due to the 3 supported steer wheels.
- Every carriage is rubber-coated to avoid damages to goods.
- Models KV for loads without legs (cabinets, cases etc.)
- Models BV for furniture with legs (tables, desks etc.)

| type | ref. no. | safe working load per set (kg) | wheel diameter (mm) | loading height (mm) | dimensions (mm) | material | weight per set (kg) |
|-------------|----------|--------------------------------|---------------------|---------------------|-----------------|----------|---------------------|
| TKV - 100 K | 4250051 | 400 | 50 x 20 | 15 | 305 x 165 x 65 | aluminum | 5.6 |
| TBV - 100 B | 4250053 | 400 | 50 x 20 | 15 | 195 x 165 x 85 | aluminum | 4.8 |
| TKV - 150 K | 4250055 | 600 | 50 x 20 | 15 | 366 x 204 x 85 | steel | 8.0 |



TR heavy machinery roller skates

V

TRS

- The steering-platform skate running on bearings makes manoeuvring with heavy loads easier.
- Length of guiding rod is 1000 mm; with transport eye.

TRW

- Roller skates can be mated by means of two connecting rods.
- Roller skates are always supplied in pairs incl. 2 connecting rods.

General

- Nylon rollers running on bearings except for models TRS-120 and TRW-240 fitted with steel rollers.
- Nylon rollers will not damage floors.
- Platforms have anti-slip rubber coatings.
- Can be easily placed or positioned by means of the hand grip.

TRS steering skates

| type | ref. no. | lifting capacity (kg) | number of rollers | material roller | roller \varnothing x width (mm) | platform dimensions L x W x H (mm) | weight (kg) |
|---------|----------|-----------------------|-------------------|-----------------|-----------------------------------|------------------------------------|-------------|
| TRS- 30 | 4250001 | 3.000 | 4 | nylon | 85 x 90 | 310 x 255 x 105 | 15 |
| TRS- 60 | 4250003 | 6.000 | 8 | nylon | 85 x 90 | 630 x 400 x 115 | 50 |
| TRS-120 | 4250005 | 12.000 | 8 | steel | 83 x 80 | 630 x 400 x 115 | 66 |



TRW roller skates

| type | ref. no. | lifting capacity per pair (kg) | number of rollers | material roller | roller \varnothing x width (mm) | platform dimensions L x B x H (mm) | weight (kg) |
|---------|----------|--------------------------------|-------------------|-----------------|-----------------------------------|------------------------------------|-------------|
| TRW- 60 | 4250011 | 6.000 | 8 | nylon | 85 x 90 | 300 x 250 x 115 | 30 |
| TRW-120 | 4250013 | 12.000 | 12 | nylon | 85 x 90 | 360 x 220 x 115 | 38 |
| TRW-240 | 4250015 | 24.000 | 16 | steel | 83 x 85 | 360 x 220 x 115 | 65 |

TS complete roller skate set for handling heavy machinery

V



Case with pull handle

REMA roller skate sets consist of 4 rollers, 2 bogies, 2 raising blocks, 2 steering rods and 2 connecting rods.

Delivered in metal storage/transport case with the appropriate pull handle.

Application

- Short, variable handling distances.
- For commissioning work and handling heavy loads.
- Due to the steering rods, large machines can be handled with ease.
- The handling speed may not exceed 5 m/min.
- Minimum turning cycle is 3 meter.



Roller skate set

| type | ref. no. | safe working load (ton) | dimensions L x W x H (mm) | roller diameter (mm) | turntable (mm) | weight (kg) |
|-------|----------|----------------------------|---------------------------------|----------------------------|-------------------|----------------|
| TS-20 | 4211003 | 20 | 120 x 120 x 108 | 18 | 130 | 50 |
| TS-30 | 4211005 | 30 | 120 x 120 x 117 | 24 | 130 | 58 |
| TS-60 | 4211007 | 60 | 130 x 130 x 140 | 30 | 150 | 92 |

TRH roller-type handspikes

V



Handspikes made of steel pipe are designed for a problem-free lifting of loads. Fitted with 2 steel rollers $\varnothing 100 \times 55$ mm.



| type | ref. no. | lifting capacity (kg) | lifting height (mm) | lever length (mm) | weight (kg) |
|----------|----------|--------------------------|------------------------|----------------------|----------------|
| TRH - 15 | 4250040 | 1500 | 200 | 2000 | 13 |