REMA®

When ordering, please supply us with flange width in mm.

Elephant MAS electric trolleys

H

Properties

- Single-pin design.
- 1 travel speed.
- Anti-tilt and wheel fracture support devices.
- Incl. a 24 V control unit and a pendant control with emergency stop.
- Convenient plug-type connection.

Motor

- Motor output: 0.4 kW.
- Duty cycle: 30%.
- Operating voltage: 400 V, 3 phase, 50 Hz.
- Insulation class: E.
- Protection class IP 54

Min. radius of curve

- type 0.5 - 1.0 = 1100 mm
- type 2.0 - 3.0 = 1500 mm





type	ref. no.	safe working load (kg)	for hoist model	speed (m/min)	flange width (mm)	dimensions in mm					wheel diameter (mm)	weight (kg)
						E	F	G	I	J		
MAS - 0.5	**0920001**	500	FAH/FBH	10	75 - 300	248	228	120	242	102	65	31
MAS - 1.0	**0920003**	1000	FAH/FBH	10	75 - 300	248	228	120	242	102	65	31
MAS - 2.0	**0920005**	2000	FAH/FBH	10	100 - 300	265	245	148	288	120	80	40
MAS - 3.0	**0920007**	3000	FAH/FBH	10	100 - 300	318	234	117	310	154	98	64