



CSVW



CSV

## CSV/CSVW spindle beam clamps

H

Suitable for lifting steel beams or can be utilized as semi-permanent lifting eyes.

### Properties

- For a quick and easy mounting of beam clamps onto beams, they are fitted with spindles.
- Model REMA CSV clamps are also available without lifting eyes (= model CSVW).
- Safety factor min. 5 x rated load capacity.
- Each sheet clamp is subject to test load at 2 x rated load capacity.

type	ref. no.	safe working load (kg)	jaw opening (mm)	weight (kg)	dimensions in mm				
					A	B	C	D	E
CSVW - 1.0	3367001	1.000	75 - 190	2.1	opening + 60	170	-	120	-
CSVW - 2.0	3367002	2.000	75 - 190	2.7	opening + 60	170	-	120	-
CSVW - 3.0	3367003	3.000	75 - 190	2.7	opening + 60	170	-	180	-
CSVW - 4.0	3367004	4.000	150 - 300	12.0	opening + 80	325	-	180	-
CSVW - 5.0	3367005	5.000	150 - 300	12.0	opening + 80	325	-	180	-
CSV - 1.0	3368001	1.000	75 - 190	3.4	opening + 60	300	75	120	16
CSV - 2.0	3368002	2.000	75 - 190	4.0	opening + 60	300	75	120	16
CSV - 3.0	3368003	3.000	75 - 190	4.0	opening + 60	300	75	120	16
CSV - 4.0	3368004	4.000	150 - 300	15.0	opening + 80	450	80	180	20
CSV - 5.0	3368005	5.000	150 - 300	15.0	opening + 80	450	80	180	20

