



## SL hand-operated stackers

500/1000 kg

V

### Properties

- Complies with EN 1757-1.
- Compact and almost maintenance-free.
- Winch fitted with load pressure brake.
- Brakeable polyurethane steering wheels  $\varnothing$  150 x 40 mm.
- Fork rollers - single : polyurethane  $\varnothing$  80 x 47 mm.
- **Model 50B** : fork width, adjustable - 160 to 690 mm.  
fork length - 1000 mm.
- **Model 100B** : fork width, non-expandable - 540 mm.  
fork length - 1150 mm.

| type     | ref. no. | safe working load (kg) | dimensions fork L x W (mm) | lifting height |           | lifting height per stroke (mm) | height (mm) | weight (kg) |
|----------|----------|------------------------|----------------------------|----------------|-----------|--------------------------------|-------------|-------------|
|          |          |                        |                            | min. (mm)      | max. (mm) |                                |             |             |
| SL - 50B | 3470101  | 500                    | 1000 x 160/690             | 90             | 1500      | 22                             | 2030        | 146         |
| SL -100B | 3470103  | 1000                   | 1150 x 540                 | 88             | 1500      | 9.5                            | 1930        | 182         |



## SH hand-operated hydraulic stackers

1000 kg

V

### Properties

- Complies with EN 1757-1.
- Hydraulic pump with overload protection.
- Lifting and controlled lowering by means of the bar.
- Steering wheels with brakes : polyurethane  $\varnothing$  150 x 50 mm.
- Fork rollers - single : polyurethane  $\varnothing$  80 x 70 mm.

| type    | ref. no. | safe working load (kg) | dimensions fork L x W (mm) | lifting height |           | lifting height per stroke (mm) | height (mm) | weight (kg) |
|---------|----------|------------------------|----------------------------|----------------|-----------|--------------------------------|-------------|-------------|
|         |          |                        |                            | min. (mm)      | max. (mm) |                                |             |             |
| SH-1015 | 3470201  | 1000                   | 1150 x 540                 | 88             | 1500      | 12.5                           | 1964        | 220         |
| SH-1025 | 3470205  | 1000                   | 1150 x 540                 | 88             | 2500      | 12.5                           | 1964        | 330         |