

HT hand-operated movable lifting tables

V



HT

An ergonomic solution for lifting parts and tools required for maintaining machines to a required operational height.

Type HT : Hand operated movable lifting tables.

Type HTE : Electrically operated movable lifting tables.

Type D : Double scissors mechanisms for an even higher elevating height.

Type K : Tilting table to facilitate an easier unloading of piece-goods from containers and crates.

Properties

- Complies with DIN 1570.
- Overflow hydraulics for a higher level of safety.
- Foot pedal for lifting (excl. type W).
- Operating handle controls lowering speed.
- REMA movable lifting tables are fitted with two rigid wheels and two steer wheels with brakes each.
- All models have rigid push rods except for Model HT-15 which is equipped with a foldable push rod.
- Type HTE with maintenance-free 70 Ah/12V battery with charger.
- Number of lifting cycles at full load: approx. 40 lifts.
- Lift duration: approx. 15 sec.

type	ref. no.	safe working load (kg)	wheel diameter (mm)	dimensions table L x W (mm)	minimum table height (mm)	maximum table height (mm)	lever height (mm)	weight (kg)
HT - 15	3460015	150	100	700 x 450	225	760	1000	41
HT - 25	3460025	250	125	815 x 500	315	910	1100	78
HT - 50	3460050	500	150	1010 x 520	430	1000	1130	118
HT - 75	3460075	750	150	1010 x 520	432	1000	1130	120
HT - 100	3460100	1000	150	1010 x 520	440	960	1130	135
HT - 50D	3460150	500	150	1010 x 520	435	1585	1130	168
HT - 80K	3460280	800	150	830 x 520	440	1000-1560	1130	145
HTE - 50	3465050	500	150	1010 x 520	440	950	1180	148
HTE - 100	3465100	1000	150	1010 x 520	490	950	1180	169
HTE - 50D	3465150	500	150	1010 x 520	495	1615	1180	198
HTE - 80K	3465280	800	150	830 x 520	495	1000-1620	1180	185



D



K



HTE

⚠ IMPORTANT

Let motor cool down for at least 3 minutes after each lifting cycle !